



вставка предохранителя PV, вкл. ножевые контакты, NH1XL, In: 100 A, gPV, Un DC: 1500 В, фронт. индикат.

версия			
торговая марка изделия	SENTRON		
наименование изделия	Плавкая вставка PV		
исполнение изделия	С ножевыми контактами		
исполнение индикатора рабочего состояния	Лобовой индикатор рабочего состояния		
исполнение плавкой вставки предохранителя	Фотовольтаический предохранитель, исполнение NH		
Общие технические данные			
типоразмер системы безопасности согласно DIN EN 60269-1	NH1XL		
эксплуатационный класс вставки предохранителя	gPV		
коэффициент переменной нагрузки (WL)	1		
тип напряжения рабочего напряжения	Постоянный ток		
напряжение питания			
напряжение питания	1 500 V		
• при постоянном токе			
Коммутационная способность			
коммутационная способность по току	30 kA		
• при постоянном токе согласно МЭК 60947-2 расчетное значение			
рассеивание			
мощность потерь [Вт]	30 W		
мощность потерь [Вт]	30 W		
• при расчетном значении тока при переменном токе в теплом рабочем состоянии на каждый полюс			
• макс.	30 W		
Механическая конструкция			
монтажное положение	произвольно, предпочтительно вертикально		
масса нетто	1 003 g		
условия окружающей среды			
окружающая температура при эксплуатации	-20 °C		
• мин.			
• макс.	50 °C		
экологическая категория	от -20 до +50 при относительной влажности 95%		
<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>Test Certificates</b>	<b>other</b>

[Confirmation](#)



[Special Test Certificate](#)

[Miscellaneous](#)

other

Environment

#### Дополнительная информация

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Информация об упаковке**

[Информация об упаковке](#)

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3NE1221-5E>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/ru/ps/3NE1221-5E>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NE1221-5E](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1221-5E)

**CAx-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

---

последнее изменение:

03.02.2023 

